



The best choice for torque screwdrivers

ABB torque settings

S200 Series MCB	2.8Nm
S280 Series MCB	2.5Nm
S800 Series MCB	3.0 - 4.0Nm (max)
F200 Series RCCB up to 100A	2.8Nm
F200 Series RCCB 125A	3Nm
DDA Addon Block for S200 Series	2.8Nm
DDA Addon Block for S800 Series	3.0 - 4.0Nm (max)
DS201/DS202C RCBO	2.8Nm
DS271 Single module RCBO	2Nm (top terminal) 1.8Nm (bottom terminal)
E200 Series Switches	2.5Nm
ESB Installation contactors	1.5Nm (Main Connections) 0.9Nm (Coil Terminals)
AF09 - AF16 Contactors	1.5Nm (Main Connections) 1.2Nm (Coil Terminals)
AF26 - AF38 Contactors	2.5Nm (Main Connections) 1.2Nm (Coil Terminals)
A9-A16 ContactorS	1.0 - 1.2Nm (Main connections) 1.0 - 1.2 Nm (Coil terminals) 1.0 - 1.2 Nm (auxiliary contacts)
A26 Contactors	1.7 - 2.2Nm (Main connections) 1.0 - 1.2Nm (Coil terminals) 1.7 - 2.2 Nm (auxiliary contacts)
A30 - A40 Contactors	2.3 -2.6Nm (Main connections) 1.0 - 1.2Nm (Coil terminals) 1.0 - 1.2 Nm (auxiliary contacts)
A45 - A70 Contactors	4.0 - 4.5Nm (Main connections) 1.0 - 1.2Nm (Coil terminals) 1.0 - 1.2 Nm (auxiliary contacts)
A95 - A110 Contactors	6.0 - 6.5Nm (Main connections) 1.0 - 1.2Nm (Coil terminals) 1.0 - 1.2 Nm (auxiliary contacts)
A145 - A185 Contactors	18.0 - 20Nm (Main connections) 1.0 - 1.2Nm (Coil terminals)
A210 - A300 Contactors	28.0 - 30Nm (Main connections) 1.0 - 1.2Nm (Coil terminals)
A400 - A460 Contactors	40.0 - 44Nm (Main connections) 1.0 - 1.2Nm (Coil terminals)
A580 - A1350 Contactors	45.0 - 49Nm (Main connections) 1.0 - 1.2Nm (Coil terminals)
EK110 Contactor	5.0 - 6Nm (Main connections) 1.0 - 1.2Nm (Coil terminals)
EK150 - EK1000	18.0 - 22Nm (Main connections) 1.0 - 1.2Nm (Coil terminals)
TF42DU.... Thermal Overloads	1.5 -2.5Nm (Main Circuit) 1.0-1.5Nm (auxiliary circuit)
TA25DU....25 Thermal overload	1.2 - 1.4Nm
TA25DU32 Thermal overload	2 - 2.4Nm
TA42DU.... Thermal overload	3 - 4 Nm
TA75DU.... Thermal overload	3 - 4 Nm
TA80DU.... Thermal overload	3 - 4 Nm
TA110DU... Thermal overload	7.2 - 9.6Nm
TA200DU.... Thermal overload	12 - 16Nm
TA450DU/SU.... Thermal overload	12 - 16Nm
Compact Pushbutton	0.8Nm (Electrical conns) 2 -2.3 Nm (locking ring)
Compact Selector Switch	0.8Nm (Electrical conns) 2 -2.3 Nm (locking ring)
Compact Pilot light	0.9Nm (Electrical conns) 2 -2.3 Nm (locking ring)
Compact Emergency Stop	0.8 Nm (Electrical conns) 2 -2.3 Nm (locking ring)
Modular range Pilot devices (All)	0.9Nm (Electrical conns) 2 -2.3 Nm (locking ring)
T1 MCCB (70mm2 Cable conns)	7Nm
T2 MCCB (Front Bar Conns)	6Nm
T3 MCCB (Front Bar Conns)	8Nm
T4 MCCB (Front Bar Conns)	18Nm
T5 MCCB (Front Bar Conns)	28Nm
T6 MCCB (Front Bar Conns)	9Nm
T7 MCCB (Front Bar Conns)	18Nm
OT16F.. - OT40F.. Switch Disconnecter	0.8Nm
OT63F.. - OT80F.. Switch Disconnecter	2Nm
OT100F.. - OT125F.. Switch Disconnecter	6Nm
OT160E Switch Disconnecter	6Nm
OT160EV Switch disconnecter	7Nm
OT200E - OT250E Switch Disconnecter	7Nm
OT315E - OT400E Switch Disconnecter	16Nm
OT630E - OT800E Switch Disconnecter	27Nm
OT1000E - OT3150E Switch Disconnecter	50 - 75Nm





The best choice for torque screwdrivers

Crabtree torque settings

Loadstar & Starbreaker (Outgoing)

All Main Switches	2.3 Nm (20 ibf-in)
All RCDs	1.7 Nm (15 ibf-in)
All MCBs	1.7 Nm (15 ibf-in)
All RCBOs	1.7 Nm (15 ibf-in)
All Earth and Neutral Terminals	1.7 Nm (15 ibf-in)

Loadstar 3 Phase Range

All Main Switches	2.3 Nm (20 ibf-in)
All RCDs	1.7 Nm (15 ibf-in)
All MCBs	1.7 Nm (15 ibf-in)
All RCBOs	1.7 Nm (15 ibf-in)
All Earth and Neutral Terminals	1.7 Nm (15 ibf-in)

Loadstar Type A Range

All Main Switches	2.3 Nm (20 ibf-in)
All RCDs	1.7 Nm (15 ibf-in)
All MCBs	1.7 Nm (15 ibf-in)
All RCBOs	1.7 Nm (15 ibf-in)
All Earth and Neutral Terminals	1.7 Nm (15 ibf-in)

Fusestar Rotary Isolators

20Amp to 40Amp	2 Nm
63Amp (small enclosure)	2 Nm
63Amp to 125Amp	3.5 Nm

Fusestar Switchfuses

M4	1.35 Nm
M5	5.5 Nm
M6	9.5 Nm
M8	17 Nm
M10	28 Nm
M12	45 Nm

Powerstar 125 & SystemPowerstar MCCB Panel Boards

All Main Switches	TBC
All MCCBs	2.5 Nm
All Earth and Neutral Terminals	TBC





The best choice for torque screwdrivers

Eaton Moeller torque settings

PLS6 MCBs	2.4Nm(max)
PLSM MCBs	2.4Nm(max)
PLHT MCBs	2.4Nm(max)
PFIM RCCBs	2.4Nm(max)
PKS6 and PKSM RCBOs	2.4Nm(max)
IS Isolators	2.5 - 5.0Nm (max)
Z-RE relays	0.8Nm (max)
Z-SCH contactors	0.6Nm (max)

Eaton torque settings

Eaton EAD MCBs	2.4Nm(max)
Eaton EMBH/EMCH/EMDH MCBs	2.4Nm(max)
Eaton EMBS/EMCS/EMDS MCBs	2.4Nm(max)
Eaton AM RCCBs	2.4Nm(max)
Eaton RCBOs	2.4Nm(max)
Eaton EMS Isolators	2.5 - 5.0Nm (max)
Eaton TAD/TAW / TDW / TE timers	0.8Nm (max)
Eaton CR contactors	0.6Nm (max)
Eaton Consumer unit N/E terminals	2.0Nm (max)





The best choice for torque screwdrivers

Hager torque settings

Consumer unit terminals

Earth & neutral terminal bars	2Nm
-------------------------------	-----

Invicts type B MCB distribution board terminals

Earth & neutral terminal bars	2Nm
Earth bolts	13Nm

Invicta MCCB panel board terminals

Earth & neutral terminal bars	4 - 6.6Nm
Earth bolts	M8 - 13Nm, M10 - 22Nm

Isolation

SB switch disconnectors	3.2Nm
-------------------------	-------

Circuit protection

MTN MCB	2Nm
NBN / NCN / NDN MCB	2Nm
HMF / HMC / HMD MCB	2Nm
RCBO	2Nm
RCCB	2Nm
x160 MCCB	6.6Nm
x250 MCCB	M8 - 13Nm
h400 - h630 MCCB	M10 - 22Nm
h800 MCCB	M10 - 22Nm

MK Electric torque settings

ALL MAIN SWITCHES	2-2.5Nm
-------------------	---------

RCBO'S	2-2.5Nm
TYPE B	2-2.5Nm
TYPE B WITH SOLID NEUTRAL	2-2.5Nm
TYPE C	2-2.5Nm

RCB'S	
TWO MODULE	2.5-3Nm
3 MODULE	2.5-3Nm
4 MODULE	2.5-3Nm

TIME SWITCHES	
ONE MODULE	2.5-3NM
2 MODULE	2.5-3NM
3 MODULE	2.5-3NM

TERMINAL BAR	1-1.5Nm
--------------	---------

MCB'S	
TYPE B	2-2.5Nm
TYPE C	2-2.5Nm





The best choice for torque screwdrivers

Newlec torque settings

All Main Switches	2.3 Nm (20 ibf-in)
NLCUSW100	2.3 Nm (20 ibf-in)
All RCDs	1.7 Nm (15 ibf-in)
NLRCD2530A	1.7 Nm (15 ibf-in)
NLRCD4030A	1.7 Nm (15 ibf-in)
NLRCD6330A	1.7 Nm (15 ibf-in)
NLRCD8030A	1.7 Nm (15 ibf-in)
NLRCD10030A	1.7 Nm (15 ibf-in)
NLRCD80100A	1.7 Nm (15 ibf-in)
NLRCD100100A	1.7 Nm (15 ibf-in)
All MCBs	1.7 Nm (15 ibf-in)
NLMB106	1.7 Nm (15 ibf-in)
NLMB110	1.7 Nm (15 ibf-in)
NLMB116	1.7 Nm (15 ibf-in)
NLMB120	1.7 Nm (15 ibf-in)
NLMB132	1.7 Nm (15 ibf-in)
NLMB140	1.7 Nm (15 ibf-in)
NLMB150	1.7 Nm (15 ibf-in)
All RCBOs	1.7 Nm (15 ibf-in)
NLRCB630A	1.7 Nm (15 ibf-in)
NLRCB1030A	1.7 Nm (15 ibf-in)
NLRCB1630A	1.7 Nm (15 ibf-in)
NLRCB2030A	1.7 Nm (15 ibf-in)
NLRCB3230A	1.7 Nm (15 ibf-in)
NLRCB4030A	1.7 Nm (15 ibf-in)
NLRCB630B	1.7 Nm (15 ibf-in)
NLRCB1030B	1.7 Nm (15 ibf-in)
NLRCB1630B	1.7 Nm (15 ibf-in)
NLRCB2030B	1.7 Nm (15 ibf-in)
NLRCB3230B	1.7 Nm (15 ibf-in)
NLRCB4030B	1.7 Nm (15 ibf-in)
NLRCB630A/2	1.7 Nm (15 ibf-in)
NLRCB1030A/2	1.7 Nm (15 ibf-in)
NLRCB1630A/2	1.7 Nm (15 ibf-in)
NLRCB2030A/2	1.7 Nm (15 ibf-in)
NLRCB3230A/2	1.7 Nm (15 ibf-in)
NLRCB4030A/2	1.7 Nm (15 ibf-in)
All Earth and Neutral Terminals	1.7 Nm (15 ibf-in)
NLCU2PSW/N	1.7 Nm (15 ibf-in)
NLCU5PSW/N	1.7 Nm (15 ibf-in)
NLCU8PSW/N	1.7 Nm (15 ibf-in)
NLCU11PSW/N	1.7 Nm (15 ibf-in)
NLCU9PSL/N	1.7 Nm (15 ibf-in)
NLCU12PSL/N	1.7 Nm (15 ibf-in)
NLCU17PSL/N	1.7 Nm (15 ibf-in)
NLCUHI244/N	1.7 Nm (15 ibf-in)
NLCUHI433/N	1.7 Nm (15 ibf-in)
NLCUHI465/N	1.7 Nm (15 ibf-in)
NLCUHI244MCB/N	1.7 Nm (15 ibf-in)
NLCUHI465MCB/N	1.7 Nm (15 ibf-in)
NLCU55DRC/N	1.7 Nm (15 ibf-in)
NLCU87DRC/N	1.7 Nm (15 ibf-in)
NLCU2PRC/N	1.7 Nm (15 ibf-in)
NLCU5PRC/N	1.7 Nm (15 ibf-in)
NLCU8PRC/N	1.7 Nm (15 ibf-in)
NLCU11PRC/N	1.7 Nm (15 ibf-in)
NLCUSHOWER/N	1.7 Nm (15 ibf-in)
NLCUGARAGE/N	1.7 Nm (15 ibf-in)
NLCU2MSW/N	1.7 Nm (15 ibf-in)
NLCU5MSW/N	1.7 Nm (15 ibf-in)
NLCU8MSW/N	1.7 Nm (15 ibf-in)
NLCU11MSW/N	1.7 Nm (15 ibf-in)
NLCU2MRC/N	1.7 Nm (15 ibf-in)
NLCU5MRC/N	1.7 Nm (15 ibf-in)
NLCU8MRC/N	1.7 Nm (15 ibf-in)





The best choice for torque screwdrivers

Volex torque settings

VCU Range

All Main Switches	2.3 Nm (20 ibf-in)
All RCDs	1.7 Nm (15 ibf-in)
All MCBs	1.7 Nm (15 ibf-in)
All RCBOs	1.7 Nm (15 ibf-in)
All Earth and Neutral Terminals	1.7 Nm (15 ibf-in)

Wylex torque settings

NH & VCU Range

All Main Switches	2.3 Nm (20 ibf-in)
All RCDs	1.7 Nm (15 ibf-in)
All MCBs	1.7 Nm (15 ibf-in)
All RCBOs	1.7 Nm (15 ibf-in)
All Earth and Neutral Terminals	1.7 Nm (15 ibf-in)

Standard Range

All Main Switches	2.3 Nm (20 ibf-in)
All Earth and Neutral Terminals	1.7 Nm (15 ibf-in)

NH 3 Phase Range

All Main Switches	2.3 Nm (20 ibf-in)
All RCDs	1.7 Nm (15 ibf-in)
All MCBs	1.7 Nm (15 ibf-in)
All RCBOs	1.7 Nm (15 ibf-in)
All Earth and Neutral Terminals	1.7 Nm (15 ibf-in)

NH Type A Range

All Main Switches	2.3 Nm (20 ibf-in)
All RCDs	1.7 Nm (15 ibf-in)
All MCBs	1.7 Nm (15 ibf-in)
All RCBOs	1.7 Nm (15 ibf-in)
All Earth and Neutral Terminals	1.7 Nm (15 ibf-in)

NHSF Rotary Isolators

20Amp to 40Amp	2 Nm
63Amp (small enclosure)	2 Nm
63Amp to 125Amp	3.5 Nm




NH Switchfuses

M4	1.35 Nm
M5	5.5 Nm
M6	9.5 Nm
M8	17 Nm
M10	28 Nm
M12	45 Nm




NH MCCB Panel Boards

All Main Switches	TBC
All MCCBs	2.5 Nm
All Earth and Neutral Terminals	TBC






Product	 Pz n°	 (mm)	 (mm)	Tightening torque (N.m)		Stripping (mm)
				Single cable	Multi cables	
Connection						
DB90	-	6	-	3.5	3.5	15
DDI	-	6	-	3.5	3.5	15
Circuit protection						
C32 (a, N, H)	-	5.5	-	2	2	12.5
C32H DC	-	5.5	-	2	2	12.5
C40 (Librio)	2	5.5	-	2	2	13
C45 (N, aD)	-	5.5	-	2	2	12.5
C60 ≤ 25 A	* UL1077	2	6.5	-	2/2.5 *	14
C60 > 25 A		2	6.5	-	3.5	14
C60 RCBO	Input Ph	2	6.5	-	2	14
	Output Ph/N	2	5.5	-	2	13
C60 UL489 tunnel terminal ≤ 25 A		2	6.5	-	2.5	14
C60 UL489 tunnel terminal > 25 A		2	6.5	-	3.5	14
C60 UL489 ring lug (Ø 5 mm)		2	6.5	-	2	-
C120 (N, H)	2	6.5	-	3.5	3.5	15
Déclit	2	5.5	-	2	2	13
DPN (a, N)	2	5.5	-	2	2	13
DT40 (ProDis)	2	5.5	-	2	2	13
DT60 (N, H) (ProDis)	2	6.5	-	3.5	4	14
i DPN (Clario)	2	5.5	-	2	2	13
IF	-	5.5	-	2		
K32a	-	5.5	-	2	2	12.5
K60N	2	6.5	-	2	4	14
NC32 (a, N)	-	5.5	-	2	2	12.5
NC45 (aD, H)	-	5.5	-	2	2	12.5
NC100 ≤ 63 A	2	6.5	-	3.5		12
NC100 > 63 A	2	6.5	-	3.5		19
NC100H UL1077 ≤ 40 A	2	6.5	-	3.5		12
NC100H UL1077 > 40 A	2	6.5	-	3.5		19
NC125 (H, N, L)	2	6.5	-	3.5		19
NG125 (a, N, H, L) ≤ 63 A	2	6.5	-	3.5	3.5	20
NG125 (a, N, H, L) > 63 A	-	-	4	6	6	20
QOE RCBO	2	5.5	-	2	2	14
SBI	2	5.5	-	2	2	
SF'clit	2	5.5	-	2	2	
SFP	2	5.5	-	2	2	
SFT	2	5.5	-	2	2	
STI	2	5.5	-	2	2	
V40H	Phase	2	6.5	-	2	2
	Neutral	1	4	-	1.8	1.8

Cable (mm ²)		Multi cable (mm ²)		Terminals			End piece (mm ²)	Tear resistance (N.m)
Flexible		Rigid		Flexible	Rigid	Tunnel	Clamp	Guard
Mini	Maxi	Mini	Maxi					
1.5	25	1.5	35			Yes		
1.5	25	1.5	35			Yes		
1	16	1	25			Yes		No
1	16	1	25			Yes		No
0.33	10	0.75	16	4x1.5/3x2.5/1x2.5+2x1.5	4x1.5/3x2.5/1x2.5+2x1.5	Yes		Yes
1	16	1	25			Yes		No
0.5	16	0.5	25	5x1.5/3x2.5/1x2.5+2x1.5	5x1.5/3x2.5/1x2.5+2x1.5	Yes		Yes
0.5	25	0.5	35	5x4/3x6/1x6+2x4	5x4/3x6	Yes		Yes
0.5	16	0.5	25	5x4/3x6/1x6+2x4	5x4/3x6	Yes		Yes
0.33	10	0.75	16	4x1.5/3x2.5/1x2.5+2x1.5	4x1.5/3x2.5/1x2.5+2x1.5	Yes		Yes
1	16	1	25			Yes		Yes
1	25	1	35			Yes		Yes
-	-	-	-	-	-	-	Lug	-
1	35	1.5	50	3x10/2x16/3x16	3x10/2x16	Yes		Yes
0.33	10	0.75	16	4x1.5/3x2.5/1x2.5+2x1.5	4x1.5/3x2.5/1x2.5+2x1.5	Yes		Yes
0.33	10	0.75	16	4x1.5/3x2.5/1x2.5+2x1.5	4x1.5/3x2.5/1x2.5+2x1.5	Yes		Yes
0.33	10	0.75	16	4x1.5/3x2.5/1x2.5+2x1.5	4x1.5/3x2.5/1x2.5+2x1.5	Yes		Yes
0.5	25	0.5	35	5x4/3x6/1x6+2x4	5x4/3x6	Yes		Yes
0.33	10	0.75	16	4x1.5/3x2.5/1x2.5+2x1.5	4x1.5/3x2.5/1x2.5+2x1.5	Yes		Yes
			16				Yes	
1	16	1	25			Yes		No
0.5	16	0.5	25	5x1.5/3x2.5/1x2.5+2x1.5	5x1.5/3x2.5/1x2.5+2x1.5	Yes		Yes
1	16	1	25			Yes		No
1	16	1	25			Yes		No
1	25	1	35			Yes		Yes
6	35	10	50			Yes		No
1	25	1	35			Yes		Yes
6	35	10	50			Yes		No
6	35	10	50			Yes		No
1	35	1.5	50	3x10/2x16/3x16	3x10/2x16	Yes		Yes
10	50	16	70	3x10/2x16/4x10/3x16/2x25	3x10/2x16/2x35	Yes		Yes
1	16	1	16			Yes		Yes
			25			Yes		
0.33	6	0.75	10	4x1.5/3x2.5/1x2.5+2x1.5	4x1.5/3x2.5/1x2.5+2x1.5	Yes		Yes
0.33	6	0.75	10	4x1.5/3x2.5/1x2.5+2x1.5	4x1.5/3x2.5/1x2.5+2x1.5	Yes		Yes
0.33	6	0.75	10	4x1.5/3x2.5/1x2.5+2x1.5	4x1.5/3x2.5/1x2.5+2x1.5	Yes		Yes
0.33	6	0.75	10	4x1.5/3x2.5/1x2.5+2x1.5	4x1.5/3x2.5/1x2.5+2x1.5	Yes		Yes

Product	 Pz n°	 (mm)	 (mm)	Tightening torque (N.m)		Stripping (mm)	
				Single cable	Multi cables		
Earth leakage protection							
Déclitc Vigi	2	5.5	-	2	2	13	
DPN Vigi (a, N)	2	5.5	-	2	2	13	
ID'clitc comb busbar direct connection	2	5.5	-	2	2	13	
ID'clitc cable connection	2	5.5	-	3.5	3.5	13	
ID'clitc 63 A (incomer, feeder, see P'clitc)	2	5.5	-	3.5	3.5	13	
ITG (ProDis) IDc (Clario) IC40 (Librio)	2	5.5	-	2	2	13	
P'clitc	2	5.5	-	2	2	13	
RCCB-80/100/125 A	2	6.5	-	3	3	11	
RCCB-ID	2	6.5	-	3.5	3.5	15	
RCCB-ID FI biconnect	2	6.5	-	3.5	3.5	15	
RCCB-type B 63 A	2	6.5	-	3.5	3.5	15	
Vigi C32, Vigi C45 and Vigi XC40	40 A	-	5.5	-	1.2	1.2	12.5
Vigi C40 (Librio)	2	5.5	-	2	2	13	
Vigi C60 (Librio)	2	5.5	-	2	2	13	
Vigi C60 c (Clario)	2	5.5	-	2	2	13	
Vigi C60 ≤ 25 A	2	6.5	-	2	4	14	
Vigi C60 ≤ 40 A and ≤ 63 A	2	6.5	-	3.5	4	14	
Vigi C63	2	6.5	-	3.5	3.5		
Vigi C120	2	6.5	-	3.5	3.5	15	
Vigi DT40 (ProDis)	2	5.5	-	2	2	13	
Vigi i DPN (Clario)	2	5.5	-	2	2	13	
Vigi NC100 ≤ 63 A	2	6.5	-	3.5		12	
Vigi NC100 > 63 A	2	6.5	-	3.5		19	
Vigi NC125	2	6.5	-	3.5		19	
Vigi NG125 ≤ 63 A	2	6.5	-	3.5	3.5	20	
Vigi NG125 > 63 A	-	-	4	6	6	20	
Vigi TG60 (ProDis)	2	5.5	-	2	2	13	
Control, Remote control							
I 20...32 A	1	5	-	1.8	1.8	10	
I 40...125 A	2	6.5	-	4.5	4.5		
I-NA	2	6.5	-	3.5	3.5	15	
IB	2	5.5	-	2			
NG125NA ≤ 63 A	2	6.5	-	3.5	3.5	20	
NG125NA > 63 A	-	-	4	6	6	20	
TC16/TC16P	Power	-	4	-	1.8	1.8	12.5
	Control	-	-	-	-	-	-
TmC60/C120	1	4	-	1	1	10	
XC40	Power	-	4	-	1.8	1.8	13.2
	Control, signal	-	3.5	-	0.4	0.4	
Motor protection							
C60 LMA ≤ 10 A	2	6.5	-	2	4	14	
C60 LMA > 12,5 A	2	6.5	-	3.5	4	14	
NC100 LMA	2	6.5	-	3.5		19	
NG125 LMA ≤ 63 A	2	6.5	-	3.5	3.5	20	
NG125 LMA > 63 A	-	-	4	6	6	20	
P25M	2	5.5	-	1.7			
Load protection							
PE	2	6.5	-	2	2	11	
PF15/8	Ph/N	2	6.5	-	1.2	1.2	11
	Earth	2	6.5	-	2	2	11
PF65/30	Ph/N	2	6.5	-	2	2	16
	Earth	2	6.5	-	3.5	3.5	16
PRC	-	3.5	-	0.4	0.4	6	
PRD	2	6.5	-	2	2	14	
PRF1/L40A	2	6.5	-	3	3	14.5	
PRI	-	3.5	-	0.4	0.4	6	
ST single pole	2	6.5	-	2	2	14	
ST multi-pole	Ph/N	2	6.5	-	2	2	14
	Earth	2	6.5	-	3.5	3.5	17

Cable (mm ²)		Multi cable (mm ²)				Terminals			End piece (mm ²)	Tear resistance (N.m)
Flexible		Rigid		Flexible	Rigid	Tunnel	Clamp	Guard		
Mini	Maxi	Mini	Maxi							
0.33	10	0.75	16	4x1.5/3x2.5/1x2.5+2x1.5	4x1.5/3x2.5/1x2.5+2x1.5	Yes		Yes		
0.33	10	0.75	16	4x1.5/3x2.5/1x2.5+2x1.5	4x1.5/3x2.5/1x2.5+2x1.5	Yes		Yes		
1	10	1	16			Yes		Yes		
1	35	1	50			Yes		Yes		
1	35	1	50			Yes		Yes		
1	10	1	16			Yes		Yes		
0.33	10	0.75	16	4x1.5/3x2.5/1x2.5+2x1.5	4x1.5/3x2.5/1x2.5+2x1.5	Yes		Yes		
1	35	1	50	2x1.5 to 16	2x1.5 to 16	Yes	Yes	No		100
1	35	1	50			Yes		Yes		100
1	35	1	50			Yes	Yes	Yes		100
1	25	1	35			Yes				100
			10			Yes		No		
0.33	10	0.75	16	4x1.5/3x2.5/1x2.5+2x1.5	4x1.5/3x2.5/1x2.5+2x1.5	Yes		Yes		
0.33	10	0.75	16	4x1.5/3x2.5/1x2.5+2x1.5	4x1.5/3x2.5/1x2.5+2x1.5	Yes		Yes		
0.33	10	0.75	16	4x1.5/3x2.5/1x2.5+2x1.5	4x1.5/3x2.5/1x2.5+2x1.5	Yes		Yes		
0.5	16	0.5	25	4x1.5/3x2.5/1x2.5+2x1.5	4x1.5/3x2.5/1x2.5+2x1.5	Yes		Yes		
0.5	25	0.5	35	5x4/3x6/1x6+2x4	5x4/3x6	Yes		Yes		
1	35	1.5	50	3x10/2x16/3x16	3x10/2x16	Yes		Yes		
0.33	10	0.75	16	4x1.5/3x2.5/1x2.5+2x1.5	4x1.5/3x2.5/1x2.5+2x1.5	Yes		Yes		
0.33	10	0.75	16	4x1.5/3x2.5/1x2.5+2x1.5	4x1.5/3x2.5/1x2.5+2x1.5	Yes		Yes		
1	25	1	35			Yes				
6	35	10	50			Yes		No		
6	35	10	50			Yes		No		
1	35	1.5	50	3x10/2x16/3x16	3x10/2x16	Yes		Yes		
10	50	16	70	3x10/2x16/4x10/3x16/2x25	3x10/2x16/2x35	Yes		Yes		
0.33	10	0.75	16	4x1.5/3x2.5/1x2.5+2x1.5	4x1.5/3x2.5/1x2.5+2x1.5	Yes		Yes		
1.5	10	1.5	10	2x2.5	2x2.5	Yes		Yes		
2.5	35	6	50			Yes		No		
1	35	1	50			Yes				
	10		10			Yes				
1	35	1.5	50	3x10/2x16/3x16	3x10/2x16	Yes		Yes		
10	50	16	70	3x10/2x16/4x10/3x16/2x25	3x10/2x16/2x35	Yes		Yes		
	16		25			Yes		No		
-	-	-	-			-	-	-	Fast-on 2.5	
	6		6	2x1.5/2x2.5	2x1.5/2x2.5	Yes				
	16		25			Yes		No		
			1.5			Yes		No		
0.5	16	0.5	25	5x1.5/3x2.5/1x2.5+2x1.5	5x1.5/3x2.5/1x2.5+2x1.5	Yes		Yes		
0.5	25	0.5	35	5x4/3x6/1x6+2x4	5x4/3x6	Yes		Yes		
1	25	1	35			Yes		No		
1	35	1.5	50	3x10/2x16/3x16	3x10/2x16	Yes		Yes		
10	50	16	70	3x10/2x16/4x10/3x16/2x25	3x10/2x16/2x35	Yes		Yes		
2x1.5	2x6	2x1	2x6				Yes			
	16		25			Yes		Yes	16	135
	10		16			Yes		Yes	10	100
	16		25			Yes		Yes	16	135
	16		25			Yes		Yes	16	135
	35		50			Yes		Yes	35	236
0.5	2.5	0.5	2.5			Yes		No	1.5	50
2.5	16	2.5	25	2x(2.5-6)	2x(2.5-10)	Yes		No	16	135
10	35	10	50			Yes		No		235
0.5	2.5	0.5	2.5			Yes		No	1.5	50
2.5	16	2.5	25	2x(2.5-6)	2x(2.5-10)	Yes		No	16	135
2.5	16	2.5	25	2x(2.5-6)	2x(2.5-10)	Yes		No	16	135
2.5	35	2.5	50	2x(2.5-10)	2x(2.5-16)	Yes		No	35	236

Product	 Pz n°	 (mm)	 (mm)	Tightening torque (N.m)		Stripping (mm)
				Single cable	Multi cables	
Auxiliaries						
ATm (Tm)	1	4	-	1	1	
C60 neutral disconnecter	1	5.5	-	1.8	1.8	
EM/RM	-	3.5	-	0.6	0.6	
Limiting module (P25M)	2	5.5	-	1.7	-	
MDU, MDI		3.5	-	1	1	
MN (C32, NC100, NC125, XC40)	-	3.5	-	1	1	
MN (C60, C120, ID, DPN)	1	5	-	1	1	9
MN (NG125)	1	4	-	1	1	10
MNx (C60, C120, ID, DPN)	1	4	-	1	1	9
MSU (C60, C120, ID, DPN)	1	4	-	1	1	9
MX+OF (C32, NC100, NC125, XC40)	-	3.5	-	1	1	
MX (C60, C120, ID, DPN)	1	5	-	1	1	9
MX+OF, MX (C60, C120, ID, DPN)	1	5	-	1	1	9
MX+OF (NG125)	1	4	-	1	1	10
MXV (NG125)	1	5	-	1		10
NO/NF (switch I)	1	5	-	1.8	1.8	10
O+F, SD, MN, MX (P25M)	1	4	-	1.4	-	
OF (C32, NC100, NC125, TC16)	-	3.5	-	1	1	
OF (C60, C120, ID, DPN)	1	4	-	1	1	9
OFsp (RCCB 80/100/125 A aux.)	1	4	-	0.8		8
OF+OF (NG125)	1	4	-	1	1	10
OF+SD (NG125)	1	4	-	1	1	10
OF+SD/OF (C60, C120, ID, DPN)	1	4	-	1	1	9
OF+SD/OF (NG125)	1	4	-	1	1	10
OF.S (ID)	1	4	-	1	1	10
SD (C32, NC100, NC125, TC16)	-	3.5	-	1	1	
SD (C60, C120, ID, DPN)	1	4	-	1	1	9
SDV (NG125)	1	5	-	1		10
Accessories						
3-hole distribution terminal 19091-19096	1	5.5	-	2		10
Connection kit for UL1077	Fixing on C60	2	6.5	-	3.5	-
	Ring lug Ø 5	2	6.5	-	2	2
Connector Barclie (14875)	2	6.5	-	2.5	2.5	14
Connector C60 (26998)						
Connector NC100-125 (27153)						
Connector NC100-125 (27148-27149)			5			
Connector NC100 aux. circuit rebranching						
Connector ProDis, Clario, Libro	2	6.5	-	2.5	2.5	14
Connector STI (14885)	2	6.5	-	2.5	2.5	14
Contact PF65r/30r	-	3.5	-	0.4	0.4	
Contact PRDr	-	3.5	-	0.4	0.4	
Dividable mounting plate	2	6.5	-	3.5	4	14
Screws nuts (NG125) 19093 (Ø 6 mm)	-	-	4	6	6	
Terminal for alu cable 27060	-	-	5	5		18
Terminal for rear connection 18528	-	-	13 flat	5		
Terminal for alu cable (NG125) 19095	-	-	4	6		
Terminal block, connector, limiting device P25M	1	4	-	1.4	-	
Transfer contact (Vigi NG125 I/S/R) SCF	1	5	-	1	1	10
Voltage tap (DJ NG125)	-	-	-	-	-	-

